

MSDS MATERIAL SAFETY DATA SHEET EURO GRADE FLEX CODE: P40-100

PRODUCT DESCRIPTION

High Build elastomeric rubberized waterproofing.
Dries to a continuous flexible membrane with exceptional adhesion.
Easy application by spray, brush or roller.
Excellent durability.
Quick drying and eco-friendly.
Excellent recoating properties.

USES

Recommended heavy duty waterproof rubberising for all types of industrial applications.
Excellent for roofs.
Excellent water-resistant properties.
Metal and wooden surfaces to be primed with appropriate primer before painting.

TECHNICAL DETAILS

TYPE	Pure Acrylic Emulsion
TEXTURE	Smooth
FINISH	Medium sheen
DRYING TIME	Surface: 1 Hour
	Hard: 4 Hours
	Recoating: 4 Hours
COLOUR	Std colours (White, Grey, Charcoal, Black, Green, Terracotta, Red)
SPECIFIC GRAVITY	+/- 1.25
VISCOSITY	95-100 KU
NV. WEIGHT	57-59%
NV. VOLUME	84-86%
COVERAGE	Approx. 0.5L/ m ² per coat depending on substrate
FLASH POINT	Non-Flammable
SHELF LIFE	6-12 Months
DILUANT	Water – not normally diluted

APPLICATION

Roller	Yes
Brush	Yes
Spray	Yes
Clean up	Water

SURFACE PREPARATION

NEW SURFACES	CEMENT FIBRE
Remove all dirt, dust and plaster splashes. Apply two coats of EURO GRADE FLEX.	
	GALVANISED SHEETS
Remove all dirt, dust and plaster splashes. Clean with Galvclean and water flush to a water break free surface. Apply acid wash and flush with clean potable water. Apply two coats of EURO GRADE FLEX	
	CROMADEK SHEETS
Remove dust and any surface contamination. Abrade surface to provide key. Apply Vynalwash primer as per specification. Apply two coats of EURO GRADE FLEX.	

GENERAL

Different substrates require specific paint systems to give the best possible results.
It is, therefore recommended that you contact a representative of **EURO RUBBER** on all your painting requirements whenever possible.

PRECAUTIONS

Not suitable for chalky/powdery surfaces.
Do not dilute with water. It reduces the hiding power.
Do not apply directly to metal.
Previously painted enamel surfaces must be suitably rubbed down or washed down with sugarsoap before applying EURO RUBBER SPRAY GRADE.
Stir well before use.
Do not paint during cold or wet weather.
Clean brushes immediately after use.

This technical data furnished is obtained from controlled laboratory tests under ideal conditions. No guarantee of any performance characteristic is given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the paint only. It is the users responsibility to confirm the currency of product data sheet